UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/529,402	03/26/2005	Dean Burfoot	5522-00002	6739
26753 7590 03/03/2009 ANDRUS, SCEALES, STARKE & SAWALL, LLP 100 EAST WISCONSIN AVENUE, SUITE 1100			EXAMINER	
			ORLANDO, AMBER ROSE	
MILWAUKEE, WI 53202			ART UNIT	PAPER NUMBER
			1797	
			MAIL DATE	DELIVERY MODE
			03/03/2009	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)			
	10/529,402	BURFOOT, DEAN			
Office Action Summary	Examiner	Art Unit			
	AMBER ORLANDO	1797			
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with the c	orrespondence address			
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DA - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period w. - Failure to reply within the set or extended period for reply will, by statute, Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tim vill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).			
Status					
Responsive to communication(s) filed on 29 Ja This action is FINAL . 2b) ☑ This Since this application is in condition for allowar closed in accordance with the practice under E	action is non-final. nce except for formal matters, pro				
Disposition of Claims					
4) ☐ Claim(s) 1,2,4-12 and 14-21 is/are pending in t 4a) Of the above claim(s) is/are withdrav 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1, 2, 4-12 and 14-21 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/or Application Papers 9) ☐ The specification is objected to by the Examinet 10) ☐ The drawing(s) filed on is/are: a) ☐ accession and accession is described to a side of the content of the	vn from consideration. r election requirement. r.	Examiner.			
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a). Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d). 11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.					
Priority under 35 U.S.C. § 119					
12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received.					
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date 01/05/2009.	4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal P 6) Other:	nte			

Art Unit: 1797

DETAILED ACTION

This action is in response to the correspondence filed 01/29/2008.

Claims 2, 6, 15, and 18 have been amended.

Claims 20 and 21 are new.

Claims 3 and 13 have been cancelled.

Claims 1, 2, 4-12 and 14-21 are rejected.

Claims 1, 2, 4-12 and 14-21 have been examined and are pending.

Claim Rejections - 35 USC § 103

- 1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 2. The factual inquiries set forth in *Graham* **v.** *John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:
 - 1. Determining the scope and contents of the prior art.
 - 2. Ascertaining the differences between the prior art and the claims at issue.
 - 3. Resolving the level of ordinary skill in the pertinent art.
 - 4. Considering objective evidence present in the application indicating obviousness or nonobviousness.
- 3. Claims 1, 2, 4-12, and 14-19 are rejected under 35 U.S.C. 103(a) as being unpatentable over Howorth US 4,531,956 in view of Marsh et al. US 3,629,999.

Art Unit: 1797

4. For claim 1, the Howorth reference discloses a sterile air trolley comprising a mobile casing having at least one air inlet in its lower region (figure 1 objects 11, 13 and 14) and a plurality of air outlets in its upper region (figure 1, object 22a, and b) and enclosing an impeller operative to move air in through the at least one inlet (column 1, lines 33-34), through a filter and out of the casing by way of the outlets, the upper region of the casing providing a substantially horizontal work surface (figure 1, objects 15, and column 2, lines 46-49), the work surface consisting essentially of air outlets, the filtered air entering the hollow work surface, and exiting the air outlets which are all over the working tray (figure 2 objects 22 a and b), forming a continuously replenished rising layer of filtered air over the work surface. The reference does not disclose the work surface having an upstanding boundary wall extending around its perimeter whereby the work surface and boundary wall form a tray, the boundary wall being hollow and extending fully around the perimeter of the work surface.

Page 3

5. The Marsh et al. reference discloses the work surface having an upstanding boundary wall extending around its perimeter whereby the work surface and boundary wall form a tray, the boundary wall extending fully around the perimeter of the work surface, and the walls emitting filtered air on all sides (figure 1, objects 36 and 28). The reference does not explicitly state the boundary wall being hollow. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have the wall being hollow since the examiner takes Official Notice of the equivalence of the wall of Marsh (objects 36 and 28) and the applicants hollow wall for their use in the air outlet art and the selection of any of these known

Art Unit: 1797

equivalents to provide an outlet for filtered air would be within the level of ordinary skill in the art.

- 6. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the Howorth reference to include the work surface having an upstanding boundary wall extending around its perimeter whereby the work surface and boundary wall forming a tray, the boundary wall extending fully around the perimeter of the work surface and the walls emitting filtered air on all sides (Marsh et al. figure 4, figure 1, objects 36 and 28) because this allows for the objects to be sterilized to be securely within the apparatus and the all over flow of sterilized air. It would be obvious to one having ordinary skill in the art at the time the invention was made that the wall of Marsh (objects 36 and 28)
- 7. For claim 2, the Howorth reference discloses the need for all over flow of sterilized air from the work surface, and forming a continuously replenished rising layer of filtered air over the work surface within the sterile zone / volume (figure 2 objects 22 a and 22b). The reference does not disclose the sterile/filtered air is directed across the work surface from all directions inwardly of the boundary wall and forms a continuously replenished rising layer of filtered air over the work surface within the sterile zone / volume defined by the boundary wall.
- 8. The Marsh et al. reference discloses the sterile/filtered air is directed across the work surface from all directions inwardly of the boundary wall and forms a continuously replenished rising layer of filtered air over the work surface within the sterile zone / volume defined by the boundary wall (column 2, lines 24-27).

Art Unit: 1797

9. It would be obvious to one having ordinary skill in the art at the time the invention was made to have modified the Howorth reference to include the sterile/filtered air being directed across the work surface from all directions inwardly of the boundary wall and forming a continuously replenished rising layer of filtered air over the work surface within the sterile zone / volume defined by the boundary wall (Marsh et al. column 2, lines 24-27) because this allows for the objects to be sterilized to be securely within the apparatus and the all over flow of sterilized air.

- 10. For claim 4, the Howorth reference discloses filtered air being emitted from the work tray on all sides (figure 2 objects 22 a and b). The reference does not disclose the all sides being in the shape of a tray that is rectangular, and with the boundary wall defining the four sides of the rectangle.
- 11. The Marsh et al. reference discloses the boundary wall defines all sides of the tray and the filtered air being emitted inwardly over the work surface from all sides (figure 4 object 36). The reference does not disclose the boundary wall in the shape of a rectangle. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have the boundary wall in the shape of a rectangle since the examiner takes Official Notice of the equivalence of the tray/boundary wall in the shape of a circle of Marsh (objects 36 and 28) and the applicants tray/boundary wall in the shape of a rectangle for their use in the air tray and outlet art and the selection of any of these known equivalents to provide an tray for surgical items and an outlet for filtered air would be within the level of ordinary skill in the art.

Art Unit: 1797

12. It would have been obvious to on having ordinary skill in the art at the time the invention was made to have modified the Howorth reference to include all sides being in the shape of a tray that is rectangular, the boundary wall defining the four sides of the rectangle, and the filtered air being emitted inwardly over the work surface from all sides (Marsh et al. figure 4 object 36) because this allows for the objects to be sterilized to be securely within the working tray.

- 13. For claim 5, the Howorth reference discloses the trolley casing is in a modular form having a base unit housing the impeller and an upper unit comprising the work surface (figures 1 objects 11 and 12, and figure 2 object 17). The reference does not disclose the work surface being tray-shaped with a boundary wall, and the upper unit being readily demountable from and re-mountable to the base unit.
- 14. The Marsh et al. reference discloses the work surface being tray-shaped with a boundary wall (figure 1 objects 36 and 28).
- 15. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the Howorth reference to include the work surface being tray-shaped with a boundary wall (Marsh et al. figure 1 objects 36 and 28) because this allows for the objects to be securely within the working tray.
- 16. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have the upper unit being readily demountable from and remountable to the base unit, since it has been held that constructing a formerly integral structure in various elements involves only routine skill in the art. *Nerwin v. Erlichtnan*, 168 USPQ 177, 179.

Art Unit: 1797

17. For claim 6, the Howorth reference does not disclose sterilized surgical instruments are set out on the work surface of the upper unit and sealed in by a film, foil or lid of barrier material that is mounted above the work surface.

- 18. The Marsh et al. reference discloses a tray that has the ability to have sterilized surgical instruments on the top of the surface, and to mount foil or a lid on the top of the tray (figure 1 objects 36 and 28). It would have been within the skill of one having ordinary skill in the art at the time the invention was made to have modified the Marsh et al. reference to include the ability to mount foil or a lip on the top of the tray in order to keep the trays contents free of dust.
- 19. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the Howorth reference to include sterilized surgical instruments set out on the work surface of the upper unit and sealed in by a film, foil or lid of barrier material that is mounted above the work surface (figure 2 objects 20 and 22) because this allows for the objects to be securely within the tray, and the contents of the tray to be free of dust.
- 20. For claims 7 and 8, the Howorth reference discloses the need for a working tray to put surgical instruments or other items place flat on the working surface (3-16). The reference discloses that the working tray could have any dimension (column 3, lines 20-24). The reference does not disclose the working surface being a rectangular tray with boundary walls higher than the instruments, the height of the boundary wall is slightly greater than the height of the any of the instruments or other items placed flat on the work surface of the tray in order to fully enshroud the same, and the height of the

Art Unit: 1797

boundary wall is on the order of 200 to 300mm while maintaining the blanket of sterile air.

- 21. The Marsh et al. reference discloses a tray with boundary walls that would be higher than the surgical instruments (figure 1 objects 28 and 36 and column 3, lines 31-43). The reference does not disclose the height of the boundary wall is on the order of 200 to 300mm while maintaining the blanket of sterile air. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have the height of the boundary wall is on the order of 200 to 300mm while maintaining the blanket of sterile air, since it has been held that where the general conditions of a claim are disclosed in the prior art, discovering the optimum or workable ranges involves only routine skill in the art. In re Aller, 105 USPQ 233. The reference does not explicitly state the boundary wall being rectangular. The reference does not disclose the boundary wall in the shape of a rectangle. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have the boundary wall in the shape of a rectangle since the examiner takes Official Notice of the equivalence of the tray/boundary wall in the shape of a circle of Marsh (objects 36 and 28) and the applicants tray/boundary wall in the shape of a rectangle for their use in the air tray and outlet art and the selection of any of these known equivalents to provide an tray for surgical items and an outlet for filtered air would be within the level of ordinary skill in the art.
- 22. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the Howorth et al. reference to include the

Art Unit: 1797

working surface being a rectangular tray with boundary walls higher than the instruments, the height of the boundary wall is slightly greater than the height of the any of the instruments or other items placed flat on the work surface of the tray in order to fully enshroud the same, and the height of the boundary wall is on the order of 200 to 300mm while maintaining the blanket of sterile air (figure 1 objects 28 and 36 and column 3, lines 31-43) because this allows for the objects to be securely within the tray and provided with a continuous flow of contaminant free airflow.

- 23. For claim 9, the Howorth reference does not disclose the rate of flow of air from the outlets is of the order of 0.4 to 0.5 meters per second, and no less than approximately 0.35 meters per second.
- 24. The Marsh et al. reference discloses the rate of flow of air from the outlets of the boundary wall (column 2, lines 30-32) is adjustable. The reference does not explicitly state is of the flow rate of air in the order of 0.4 to 0.5 meters per second, and no less than approximately 0.35 meters per second. It would be obvious to one having ordinary skill in the art at the time the invention was made that the speed at which the air exits is merely a design choice and is within the abilities of the Marsh et al. reference. Furthermore it would have been obvious to one having ordinary skill in the art at the time the invention was made to have the flow rate of air in the order of 0.4 to

the time the invention was made to have the flow rate of air in the order of 0.4 to 0.5 meters per second, and no less than approximately 0.35 meters per second, since it has been held that where the general conditions of a claim are disclosed in the prior art, discovering the optimum or workable ranges involves only routine skill in the art. *In re Aller*, 105 USPQ 233

Art Unit: 1797

25. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the Howorth reference to include the rate of flow of air from the outlets is of the order of 0.4 to 0.5 meters per second, and no less than approximately 0.35 meters per second (Marsh et al. column 2, lines 30-32) because this provides laminar air flow.

- 26. For claim 10 the Howorth et al. reference discloses the work tray being densely perforated with many substantially uniform distributed apertures to provide a substantially uniform flow of air through the work tray (figure 2 objects 22 a, b and 15). The reference does not disclose the work tray comprising boundary walls which are densely perforated to provide substantially uniform air through the work tray.
- 27. The Marsh et al. reference discloses the work tray comprising boundary walls which are densely perforated to provide substantially uniform air through the work tray (figure 1 object 36 and column 2, lines 24-37).
- 28. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the Howorth reference to include the work tray comprising boundary walls which are densely perforated to provide substantially uniform air through the work tray (Marsh et al. figure 1 object 36 and column 2, lines 24-37) because this allows for the objects to be securely within the tray and a supply of substantially contaminant free air flowing over the tray.
- 29. For claim 11, the Howorth reference does not explicitly state the construction of the part of the boundary wall comprising the outlets is such as to provide a pressure drop of the order of at least 10 Pascal's. It would have been obvious to one having

Art Unit: 1797

ordinary skill in the art at the time the invention was made to the construction of the part of the boundary wall comprising the outlets is such as to provide a pressure drop of the order of at least 10 Pascal's, since it has been held that discovering an optimum value of a result effective variable involves only routine skill in the art. In re Boesch, 617 F.2d 272, 205 USPQ 215 (CCPA 1980).

- 30. For claim 12, the Howorth reference discloses a sterile air trolley having a sterile air cabinet comprising a casing having at least one air inlet in its lower region (figure 1 objects 11, 13 and 14) and a plurality of air outlets in its upper region (figure 1, object 22a, and b) and enclosing an impeller operative to move air in through the at least one inlet (column 1, lines 33-34), through a filter and out of the casing by way of the outlets, the upper region of the casing providing a substantially horizontal work surface (figure 1, objects 15, and column 2, lines 46-49), the work surface consisting essentially of air outlets, the filtered air entering the hollow work surface, and exiting the air outlets which are all over the working tray (figure 2 objects 22 a and b), forming a continuously replenished rising layer of filtered air over the work surface. The reference does not disclose the work surface having an upstanding boundary wall extending around its perimeter whereby the work surface and boundary wall form a tray, the boundary wall being hollow and extending fully around the perimeter of the work surface.
- 31. The Marsh et al. reference discloses the work surface having an upstanding boundary wall extending around its perimeter whereby the work surface and boundary wall form a tray, the boundary wall extending fully around the perimeter of the work surface, and the walls emitting filtered air on all sides (figure 1, objects 36 and 28). The

Art Unit: 1797

reference does not explicitly state the boundary wall being hollow. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have the wall being hollow since the examiner takes Official Notice of the equivalence of the wall of Marsh (objects 36 and 28) and the applicant's hollow wall for their use in the air outlet art and the selection of any of these known equivalents to provide an outlet for filtered air would be within the level of ordinary skill in the art.

- 32. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the Howorth reference to include the work surface having an upstanding boundary wall extending around its perimeter whereby the work surface and boundary wall forming a tray, the boundary wall extending fully around the perimeter of the work surface and the walls emitting filtered air on all sides (Marsh et al. figure 4, figure 1, objects 36 and 28) because this allows for the objects to be sterilized to be securely within the apparatus and the all over flow of sterilized air. It would be obvious to one having ordinary skill in the art at the time the invention was made that the wall of Marsh (objects 36 and 28)
- 33. For claim 14, the Howorth reference discloses a sterile air trolley comprising a mobile casing having at least one air inlet in its lower region (figure 1 objects 11, 13 and 14) and a plurality of air outlets in its upper region (figure 1, object 22a, and b) and enclosing an impeller operative to move air in through the at least one inlet (column 1, lines 33-34), through a filter and out of the casing by way of the outlets, the upper region of the casing providing a substantially horizontal work surface (figure 1, objects 15, and

Art Unit: 1797

column 2, lines 46-49), the work surface consisting essentially of air outlets, the filtered air entering the hollow work surface, and exiting the air outlets which are all over the working tray (figure 2 objects 22 a and b), forming a continuously replenished rising layer of filtered air over the work surface. The reference does not disclose the work surface having an upstanding boundary wall extending around its perimeter whereby the work surface and boundary wall form a tray, the boundary wall being hollow and extending fully around the perimeter of the work surface, and the air outlets facing only substantially inwardly towards the work surface from the boundary wall.

- 34. The Marsh et al. reference discloses the work surface having an upstanding boundary wall extending around its perimeter whereby the work surface and boundary wall form a tray, the boundary wall extending fully around the perimeter of the work surface, the walls emitting filtered air on all sides, and the air outlets facing only substantially inwardly towards the work surface from the boundary wall (figure 1, objects 36 and 28 column 2, lines 24-27). The reference does not explicitly state the boundary wall being hollow. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have the wall being hollow since the examiner takes Official Notice of the equivalence of the wall of Marsh (objects 36 and 28) and the applicants hollow wall for their use in the air outlet art and the selection of any of these known equivalents to provide an outlet for filtered air would be within the level of ordinary skill in the art.
- 35. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the Howorth reference to include the work surface

Art Unit: 1797

having an upstanding boundary wall extending around its perimeter whereby the work surface and boundary wall forming a tray, the boundary wall extending fully around the perimeter of the work surface, the walls emitting filtered air on all sides and the air outlets facing only substantially inwardly towards the work surface from the boundary wall (Marsh et al. figure 4, figure 1, objects 36 and 28, and column 2, lines 24-27) because this allows for the objects to be sterilized to be securely within the apparatus and the all over flow of sterilized air.

- 36. For claim 15, the Howorth reference discloses the need for all over flow of sterilized air from the work surface, and forming a continuously replenished rising layer of filtered air over the work surface within the sterile zone / volume (figure 2 objects 22 a and 22b). The reference does not disclose the sterile/filtered air is directed across the work surface from all directions inwardly of the boundary wall and forms a continuously replenished rising layer of filtered air over the work surface within the sterile zone / volume defined by the boundary wall.
- 37. The Marsh et al. reference discloses the sterile/filtered air is directed across the work surface from all directions inwardly of the boundary wall and forms a continuously replenished rising layer of filtered air over the work surface within the sterile zone / volume defined by the boundary wall (figure 1 objects 28 and 36, column 2, lines 24-37 and abstract).
- 38. It would be obvious to one having ordinary skill in the art at the time the invention was made to have modified the Howorth reference to include the sterile/filtered air is directed across the work surface from all directions inwardly of the boundary wall and

Art Unit: 1797

forms a continuously replenished rising layer of filtered air over the work surface within the sterile zone / volume defined by the boundary wall (Marsh et al. figure 1 objects 28 and 36, column 2, lines 24-37 and abstract) because this allows for the objects to be sterilized to be securely within the apparatus and the sterilized air to be distributed over the entire surface of the apparatus.

- 39. For claim 16, the Howorth reference discloses filtered air being emitted from the work tray on all sides (figure 2 objects 22 a and b). The reference does not disclose the all sides being in the shape of a tray that is rectangular, and with the boundary wall defining the four sides of the rectangle.
- 40. The Marsh et al. reference discloses the boundary wall defines all sides of the tray and the filtered air being emitted inwardly over the work surface from all sides (figure 4 object 36). The reference does not disclose the boundary wall in the shape of a rectangle. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have the boundary wall in the shape of a rectangle since the examiner takes Official Notice of the equivalence of the tray/boundary wall in the shape of a circle of Marsh (objects 36 and 28) and the applicants tray/boundary wall in the shape of a rectangle for their use in the air tray and outlet art and the selection of any of these known equivalents to provide an tray for surgical items and an outlet for filtered air would be within the level of ordinary skill in the art.
- 41. It would have been obvious to on having ordinary skill in the art at the time the invention was made to have modified the Howorth reference to include all sides being in

Art Unit: 1797

the shape of a tray that is rectangular, the boundary wall defining the four sides of the rectangle, and the filtered air being emitted inwardly over the work surface from all sides (Marsh et al. figure 4 object 36) because this allows for the objects to be sterilized to be securely within the working tray.

- 42. For claim 17, the Howorth reference discloses the trolley casing is in a modular form having a base unit housing the impeller and an upper unit comprising the work surface (figures 1 objects 11 and 12, and figure 2 object 17). The reference does not disclose the work surface being tray-shaped with a boundary wall, and the upper unit being readily demountable from and re-mountable to the base unit.
- 43. The Marsh et al. reference discloses the work surface being tray-shaped with a boundary wall (figure 1 objects 28 and 36).
- 44. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the Howorth reference to include the work surface being tray-shaped with a boundary wall (Marsh et al. figure 1 objects 28 and 36) because this allows for the objects to be securely within the working tray.
- 45. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have the upper unit being readily demountable from and remountable to the base unit, since it has been held that constructing a formerly integral structure in various elements involves only routine skill in the art. *Nerwin v. Erlicnrnan,* 168 USPQ 177, 179.

Art Unit: 1797

46. For claim 18, the Howorth reference does not disclose sterilized surgical instruments are set out on the work surface of the upper unit and sealed in by a film, foil or lid of barrier material that is mounted above the work surface.

- 47. The Marsh et al. reference discloses a tray that has the ability to have sterilized surgical instruments on the top of the surface, and to mount foil or a lid on the top of the tray (figure 1 objects 36 and 28). It would have been within the skill of one having ordinary skill in the art at the time the invention was made to have modified the Marsh et al. reference to include the ability to mount foil or a lip on the top of the tray in order to keep the trays contents free of dust.
- 48. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the Howorth reference to include sterilized surgical instruments set out on the work surface of the upper unit and sealed in by a film, foil or lid of barrier material that is mounted above the work surface (figure 2 objects 20 and 22) because this allows for the objects to be securely within the tray, and the contents of the tray to be free of dust.
- 49. For claim 19, the Howorth reference discloses the need for a working tray to put surgical instruments or other items place flat on the working surface (3-16). The reference discloses that the working tray could have any dimension (column 3, lines 20-24). The reference does not disclose the working surface being a rectangular tray with boundary walls higher than the instruments, the height of the boundary wall is slightly greater than the height of the any of the instruments or other items placed flat on the work surface of the tray in order to fully enshroud the same.

Art Unit: 1797

50. The Marsh et al. reference discloses a tray with boundary walls that would be higher than the surgical instruments (figure 1 objects 28 and 36 and column 3, lines 31-43). The reference does not explicitly state the boundary wall being rectangular. The reference does not disclose the boundary wall in the shape of a rectangle. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have the boundary wall in the shape of a rectangle since the examiner takes Official Notice of the equivalence of the tray/boundary wall in the shape of a circle of Marsh (objects 36 and 28) and the applicants tray/boundary wall in the shape of a rectangle for their use in the air tray and outlet art and the selection of any of these known equivalents to provide an tray for surgical items and an outlet for filtered air would be within the level of ordinary skill in the art.

- 51. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the Howorth et al. reference to include the working surface being a rectangular tray with boundary walls higher than the instruments, and the height of the boundary wall is slightly greater than the height of the any of the instruments or other items placed flat on the work surface of the tray in order to fully enshroud the same(Marsh et al. figure 1 objects 28 and 36 and column 3, lines 31-43) because this allows for the objects to be securely within the tray and provided with a continuous flow of contaminant free airflow.
- 52. For claims 20 and 21, the Howorth et al. reference does not disclose air outlets not being directed upwardly or outwardly.

Art Unit: 1797

53. The Marsh et al. reference discloses no air outlets being directed upwardly or outwardly (figure 4 object 36 and column 2, lines 24-37).

54. It would have been obvious to one having ordinary skill in the art at the time the invention was made to have modified the Howorth et al. reference to include no air outlets being directed upwardly or outwardly (Marsh et al. figure 4 object 36 and column 2, lines 24-37) because this provides a continuous flow of contaminant free air over the enclosed area.

Response to Arguments

- 55. Applicant's arguments, see pages 6 and 7, filed 01/29/2009, with respect to claims 2, 6, 9, 15 and 18 have been fully considered and are persuasive. The objection of claims 2, 6, 9, 15 and 18 has been withdrawn
- 56. Applicant's arguments, see pages 7-10, filed 1/29/2009, with respect to the rejection(s) of claim(s) 1, 12 and 14 under 35 U.S.C 103 (a) have been fully considered and are persuasive. Therefore, the rejection has been withdrawn. However, upon further consideration, a new ground(s) of rejection is made in view of Howorth US 4,531,956 and Marsh et al. US 3,629,999.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to AMBER ORLANDO whose telephone number is (571)270-3149. The examiner can normally be reached on Mon.-Thurs. (6:30-5:00).

Art Unit: 1797

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Walter Griffin can be reached on (571) 272-1447. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

AO

/Walter D. Griffin/ Supervisory Patent Examiner, Art Unit 1797